

09782504-062501

RI.126

38

25. A transflective liquid crystal display comprising:
a liquid crystal disposed between a front substrate
and a rear substrate,

a front polariser located in front of the front
substrate and rear polariser located behind the rear
substrate,

a front retarder located between the front substrate
and the front polariser, and

a rear retarder located between the rear substrate
and the rear polariser, and addressing means for addressing
each pixel and switching each pixel between different
states resulting in different levels of transmission of
light through the display, characterised in that,

a light source is located behind the rear polariser,
and

the liquid crystal display is provided with a rear
electrode which is partially reflective and partially
transmissive and the liquid crystal is divided into a
plurality of pixels.

39

26. A transflective display as claimed in claim 25, wherein

Q1
Cont'd

the front retarder is an achromatic combination retarder.

⁴⁰
27. A transflective display as claimed in claim 25, wherein the front retarder comprises a front halfwave plate and a front quarterwave plate.

⁴¹
28. A transflective display as claimed in claim 27, wherein the front quarterwave plate has a slow axis substantially parallel or normal to a bisetrix of surface alignment directions of the liquid crystal, such that a retardation of the front quarterwave plate, in conjunction with the retardation of the liquid crystal, produces in one state circular polarised light after a single pass.

⁴²
29. A transflective display as claimed in claim 27, wherein the front quarterwave plate has a slow axis substantially parallel or normal to a bisetrix of surface alignment directions of the liquid crystal, such that a retardation of the front quarterwave plate, in conjunction with the retardation of the liquid crystal, produces in a second state linear polarised light after a single pass.

⁴³
30. A transflective display as claimed in claim 27, wherein

09787594-062501

Q1
contd

the front quarterwave plate has a retardation of between 50nm and 250 nm.

44
31. A transflective display as claimed in claim 25, wherein the rear retarder comprises a rear quarterwave plate.

45
32. A transflective display as claimed in claim 31, wherein the rear quarterwave plate has a slow axis substantially parallel or normal to a bisetrix of surface alignment directions of the liquid crystal, such that a retardation of the rear quarterwave plate, in conjunction with the retardation of the liquid crystal and the front quarterwave plate, produces in one state circular polarised light after a single pass.

57
57
46
33. A transflective display as claimed in claim 27, wherein the rear retarder comprises a rear quarterwave plate, and the rear quarterwave plate has a slow axis substantially parallel or normal to a bisetrix of surface alignment directions of the liquid crystal, such that a retardation of the rear quarterwave plate, in conjunction with the retardation of the liquid crystal and the front quarterwave plate, produces in a second state linear polarised light

a1
Contd

after a single pass.

h.1.126 47. A transreflective display as claimed in claim 31, wherein the rear quarterwave plate has a retardation of between 100nm and 180nm.

48 25. A transreflective display as claimed in claim 25, wherein the rear substrate is provided with a partially reflective and partially transmissive mirror.

49 26. A transreflective display as claimed in claim 25 wherein the rear retarder further comprises a rear halfwave plate.

50 30. A transreflective display as claimed in claim 30, wherein the rear retarder further comprises a rear halfwave plate and the rear halfwave plate is located between the rear quarterwave plate and the rear polariser.

51 38. A transreflective display comprising a liquid crystal divided into a plurality of pixels, addressing means for addressing each pixel and swithing each pixel between different states resulting in different levels of transmission of light through the display, a flashing

09787594-062501

Al
Contd

backlight located behind the liquid crystal, and a partially reflective mirror located between the liquid crystal and the backlight for both reflecting ambient light back through the liquid crystal and allowing transmission of light from the backlight through the liquid crystal, characterised in that each pixel is provided with a light filter, and the backlight comprises a plurality of sequentially flashing light sources.

RI.126 52
39. A transflective display as claimed in claim 38, wherein each light filter is a colour light filter, and wherein said sequentially flashing light sources are of different colours.

53
40. A transflective display as claimed in claim 39, wherein said liquid crystal is part of an active matrix display.

54
41. A transflective display as claimed in claim 38, wherein the liquid crystal forms a Pi or OCB cell.

55
42. A transflective display as claimed in claim 38, wherein each said sequentially flashing light source is

09787594-06501
105290-16578460

AI
Contd

a light emitting diode (LED).

R.1.126 56
53.

A transflective display as claimed in claim 39, wherein each colour filter provides a varying level of absorption across its area.

57
44.

A transflective display as claimed in claim 43, wherein each colour filter has a transparent region.

58
45.

A transflective display as claimed in claim 44, wherein said liquid crystal is provided with a plurality of partially reflective electrodes each having a light transmissive area, and wherein each said transmissive area is optically aligned with a transparent region of one of said colour filters.

59
46.

A transflective display as claimed in claim 38, wherein the transflective liquid crystal display comprises a liquid crystal disposed between a front substrate and a rear substrate,

a front polariser located in front of the front substrate and rear polariser located behind the rear substrate,

09787594-06501
105290-465260

al
cont'd

a front retarder located between the front substrate and the front polariser, and

a rear retarder located between the rear substrate and the rear polariser, and addressing means for addressing each pixel and switching each pixel between different states resulting in different levels of transmission of light through the display, characterised in that,

a light source is located behind the rear polariser, and

the liquid crystal display is provided with a rear electrode which is partially reflective and partially transmissive and the liquid crystal is divided into a plurality of pixels.

RMS26

⁶⁰
~~47~~. A transflective display as claimed in claim 35, wherein said partially reflective and partially transmissive mirror comprises a plurality of gaps or holes.

⁶¹
~~48~~. A transflective display as claimed in claim 38, wherein said partially reflective and partially transmissive mirror comprises a plurality of gaps or holes.

⁶²
~~49~~. A transflective display as claimed in claim 35,

105290-45482501

all
cont'd

wherein said partially reflective and partially transmissive mirror is a mirror transparent to a predetermined value between 10 and 90%.

⁶³
50. A transflective display as claimed in claim 38, wherein said partially reflective and partially transmissive mirror is a mirror transparent to a predetermined value between 10 and 90%.

⁶⁴
51. A transflective display as claimed in claim 39, wherein for transmission, transflective and reflection modes of the transflective display a voltage level for each said different colour is individually adjusted.

⁶⁵
52. A transflective display as claimed in claim 25, wherein said front and rear polarisers are parallel polarisers.

⁶⁶
53. A transflective display as claimed in claim 38, wherein said front and rear polarisers are parallel polarisers.

⁶⁷
54. A transflective display as claimed in claim 25, wherein said front and rear polarisers are crossed polarisers.

09787594-062501

Al
Contd

⁶⁸
~~55.~~ A transflective display as claimed in claim 38, wherein said front and rear polarisers are crossed polarisers.

⁶⁹
~~56.~~ A transflective display as claimed in claim 25, in which the effective retardation of the nematic LC is continuously switchable, and, the two front retarders function together as an achromatic combination retarder.

⁷⁰
~~57.~~ A transflective display as claimed in claim 38, in which the effective retardation of the nematic LC is continuously switchable, and, the two front retarders function together as an achromatic combination retarder.

⁷¹
~~58.~~ A transflective display as claimed in claim 25, in which the effective retardation of the nematic LC is continuously switchable, and, the two rear retarders function together as an achromatic combination retarder.

⁷²
~~59.~~ A transflective display as claimed in claim 38, in which the effective retardation of the nematic LC is continuously switchable, and, the two rear retarders function together as an achromatic combination retarder.

09787594-06501
T05290-46549460

a1
Contd

09787594-063501

R.1.126 73
60.

A transflective display as claimed in claim 25, in which the front quarter wave plate has its slow axis substantially normal or parallel to the bisectrix of the surface director orientations of the nematic LC, and the two front retarders form an achromatic combination retarder, and the combination retarder is modified to compensate for the residual retardation of the LC at finite voltages.

74
61.

A transflective display as claimed in claim 38, in which the front quarter wave plate has its slow axis substantially normal or parallel to the bisectrix of the surface director orientations of the nematic LC, and the two front retarders form an achromatic combination retarder, and the combination retarder is modified to compensate for the residual retardation of the LC at finite voltages.

75
62.

A transflective display as claimed in claim 25, in which the rear quarter wave plate has its slow axis substantially normal or parallel to the bisectrix of the surface director orientations of the nematic LC, and the two rear retarders form an achromatic combination retarder, and the combination retarder is modified to compensate for the

Al
Contd

residual retardation of the LC at finite voltages.

76
R1.126 53. A transflective display as claimed in claim 38, in which the rear quarter wave plate has its slow axis substantially normal or parallel to the bisectrix of the surface director orientations of the nematic LC, and the two rear retarders form an achromatic combination retarder, and the combination retarder is modified to compensate for the residual retardation of the LC at finite voltages.

77
24. A transflective display as claimed in claim 25, which the nematic LC has antiparallel surface director orientation with surface pretilt, and the front substrate functions as a colour filter plate.

78
25. A transflective display as claimed in claim 38, which the nematic LC has antiparallel surface director orientation with surface pretilt, and the front substrate functions as a colour filter plate.

79
26. A transflective display as claimed in claim 25, which the red, green and blue voltage levels are individually adjusted for transmission, transflective or reflection

09787594-062501
"05290" 46528250

al
 end

modes, and the transmission/reflection against voltage curve is wavelength dependent and is different between the reflective and the transmissive mode.

21126 ⁸⁰₈₇. A transflective display as claimed in claim 38, which the red, green and blue voltage levels are individually adjusted for transmission, transflective or reflection modes, and the transmission/reflection against voltage curve is wavelength dependent and is different between the reflective and the transmissive mode.

⁸¹₈₈. A transflective display as claimed in claim 38, in which the nematic LC has substantially parallel surface director orientations.

⁸²₈₉. A transflective display as claimed in claim 68, in which the nematic LC is formed from a Pi cell.